
BOP - BLOW OUT PREVENTER HOSE

BOP - BLOW OUT PREVENTER

APPLICATION Drilling Rig Blow Out Preventer Hose.
TUBE Black, oil resistant nitrile rubber.
REINFORCEMENT Two high tensile steel wire braids.
COVER Extra heavy fire resistant neoprene rubber.
TEMPERATURE (-40°C to +120°C), (-40°F to 248°F)

Tested to Lloyd's & ERCB requirements of 700°C (130 0°F) over open flame for minimum 5 minutes.

Part No.	I.D. in	I.D. mm	O.D. in	O.D. mm	Max. W.P. psi	Min. Burst psi	Weight lbs./ft.	Coupling Series
S510-06	3/8"	9.5	1.13	28.7	3000	12000	.78	K
S510-08	1/2"	12.7	1.20	30.5	3000	12000	.84	K
S510-12	3/4"	19.1	1.50	38.1	3000	12000	1.25	K
S510-16	1"	25.4	1.85	47.0	3000	12000	1.75	K

OILFIELD KELLY HOSE

KELLY HOSE - 2"

APPLICATION Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.
TUBE Nitrile
REINFORCEMENT Four spirals of high tensile wire.
COVER Black neoprene, MSHA approved.
TEMPERATURE (-40°C to +121°C), (-40°F to +250°F)

Part No.	I.D. in	I.D. mm	O.D. in	O.D. mm	Max. W.P. psi	Min. Burst psi	Min. Bend Radius (in)	Min. Bend Radius (mm)	Weight lbs./ft.	Coupling Series
S920-32	2	50.8	2.68	68.1	3600	14400	25.0	635	2.78	X

GREASE HOSE

S020 GREASE HOSE

APPLICATION Petroleum based hydraulic fluids, water, and a wide range of chemicals.
TUBE Polyester
REINFORCEMENT One braid, synthetic fiber.
COVER Black polyurethane.
TEMPERATURE (-40°C to +100°C), (-40°F to +212°F)

Part No.	I.D. in	I.D. mm	O.D. in	O.D. mm	Max. W.P. psi	Min. Burst psi	Min. Bend Radius (in)	Min. Bend Radius (mm)	Weight lbs./ft.	Coupling Series
S020-02	1/8	3.2	.34	8.6	3000	12000	.50	13	.03	K